

Matrix™

2000 Stand-alone Payout Module

Up to 1.65
cm/se

Pneumatic Air Chuck Control

Super simple lock & unlock
of material payout reel

Pneumatic Air Chuck

Clockwise or counter-clockwise
rotation for top or bottom payout

Mobile Stand

Stable welded frame
with locking casters

Warranty: 12 Months

The *Matrix 2000* feeds web material from a reel, rotating either clockwise or counter-clockwise, on a motorized hub with a sensor-monitored tension-free loop

[Request a Quote](#)

* material reel not included

Matrix™

2000 Stand-alone Payout Module

Capacities

- Air chuck hub diameter: 15.2 cm
- Material reel max weight: 23 kg

Performance

- Rate up to 1.65 cm/sec

Facilities Requirements

- Power: 100-125 VAC, 1 Φ , 50-60 Hz, 4 A
- -or- 220-245 VAC, 1 Φ , 50-60 Hz, 2 A
- Process Air: 28 lpm @ 3.4 bar

Dimensional Specifications (approx.)

- Size: 79 cm W x 82 cm D x 118 cm H
- Weight: 97 kg

Key Features

- Automatic start & stop of material payout
- Clockwise or counter-clockwise payout
- Pneumatic air chuck
- Adjustable loop sensor location - top or bottom material feed

Options

- Optional data signal for material ready
- Optional air chuck hub diameters available



Top Feed Sensor



Bottom Feed Sensor



*Optional Data Signal Connection
For Material Ready*



Specifications subject to change without notice